

Oil & Gas Industry

Rotating equipment: Separators & Centrifuges for Oil Processing

Prevent loosening and corrosion of the bowl fasteners to ensure reliability of gasket between head wall, cylindrical bowl and bowl beach by applying **LOCTITE 243** or **LOCTITE 248 Medium Strength Threadlocker**



Seal and lock fittings and piping of the grease lubrication system at any angle with Thread Sealants **LOCTITE 577** or **LOCTITE 572**



Prevent loosening and corrosion of drive, V-belt pulley, V-belt guard fasteners by applying **LOCTITE Threadlocker**



Prevent corrosion and seizure of alignment pins with **LOCTITE LB 8009 Heavy Duty Anti Seize**. Prevent loosening and corrosion of bearing block fastener with **LOCTITE 270 Threadlocker**.



Control noise by using **TEROSON Terodem Soundproofing Material** on the base frame and V-belt guard

Seal the flange faces of bowl components with **LOCTITE 5188 Flange Sealant**. Rebuild worn flange surfaces with **LOCTITE EA 3478 Superior Metal**



Bond the artificial turf or other attachments with **LOCTITE EA 9492 High Temperature – Multi Purpose Epoxy** onto the bowl inside surface



Retain the joint between the bearings of bowl and conveyor using **LOCTITE 603** or **LOCTITE 641 Retaining Compound**

